
python-semver Documentation

Release 2.10.0

Kostiantyn Rybnikov and all

May 05, 2020

1	Quickstart	1
2	Installing semver	3
2.1	Pip	3
2.2	Linux Distributions	3
3	Using semver	5
3.1	Knowing the Implemented semver.org Version	5
3.2	Creating a Version	5
3.3	Parsing a Version String	6
3.4	Checking for a Valid Semver Version	7
3.5	Accessing Parts of a Version Through Names	7
3.6	Accessing Parts Through Index Numbers	8
3.7	Replacing Parts of a Version	8
3.8	Converting a VersionInfo instance into Different Types	9
3.9	Raising Parts of a Version	9
3.10	Increasing Parts of a Version Taking into Account Prereleases	10
3.11	Comparing Versions	10
3.12	Comparing Versions through an Expression	12
3.13	Getting Minimum and Maximum of two Versions	12
3.14	Dealing with Invalid Versions	12
3.15	Replacing Deprecated Functions	14
3.16	Displaying Deprecation Warnings	15
4	pysemver 2.10.0	17
4.1	Synopsis	17
4.2	Description	17
4.3	Commands	17
4.4	Return Code	19
4.5	See also	19
5	Contributing to semver	21
5.1	Reporting Bugs and Feedback	21
5.2	Fixing Bugs and Implementing New Features	21
5.3	Modifying the Code	21
5.4	Running the Test Suite	22
5.5	Documenting semver	23

6	API	25
7	Change Log	35
7.1	Version 2.10.0	35
7.2	Version 2.9.1	36
7.3	Version 2.9.0	37
7.4	Version 2.8.2	38
7.5	Version 2.8.1	38
7.6	Version 2.8.0	38
7.7	Version 2.7.9	39
7.8	Version 2.7.8	39
7.9	Version 2.7.7	39
7.10	Version 2.7.2	39
7.11	Version 2.6.0	40
7.12	Version 2.5.0	40
7.13	Version 2.4.2	40
7.14	Version 2.4.1	40
7.15	Version 2.4.0	41
7.16	Version 2.3.1	41
7.17	Version 2.3.0	41
7.18	Version 2.2.1	41
7.19	Version 2.2.0	42
7.20	Version 2.1.2	42
7.21	Version 2.1.1	42
7.22	Version 2.1.0	42
7.23	Version 2.0.2	43
7.24	Version 2.0.1	43
7.25	Version 2.0.0	43
7.26	Version 0.0.2	44
7.27	Version 0.0.1	44
8	Indices and Tables	45
	Python Module Index	47
	Index	49

CHAPTER 1

Quickstart

A Python module for [semantic versioning](#). Simplifies comparing versions.

Warning: As anything comes to an end, this project will focus on Python 3.x only. New features and bugfixes will be integrated into the 3.x.y branch only.

Major version 3 of semver will contain some incompatible changes:

- removes support for Python 2.7 and 3.3
- removes deprecated functions.

The last version of semver which supports Python 2.7 and 3.4 will be 2.10.x. However, keep in mind, version 2.10.x is frozen: no new features nor backports will be integrated.

We recommend to upgrade your workflow to Python 3.x to gain support, bugfixes, and new features.

The module follows the MAJOR.MINOR.PATCH style:

- MAJOR version when you make incompatible API changes,
- MINOR version when you add functionality in a backwards compatible manner, and
- PATCH version when you make backwards compatible bug fixes.

Additional labels for pre-release and build metadata are supported.

To import this library, use:

```
>>> import semver
```

Working with the library is quite straightforward. To turn a version string into the different parts, use the `semver.VersionInfo.parse` function:

```
>>> ver = semver.VersionInfo.parse('1.2.3-pre.2+build.4')
>>> ver.major
1
>>> ver.minor
2
>>> ver.patch
3
>>> ver.prerelease
'pre.2'
>>> ver.build
'build.4'
```

To raise parts of a version, there are a couple of functions available for you. The function `semver.VersionInfo.bump_major` leaves the original object untouched, but returns a new `semver.VersionInfo` instance with the raised major part:

```
>>> ver = semver.VersionInfo.parse("3.4.5")
>>> ver.bump_major()
VersionInfo(major=4, minor=0, patch=0, prerelease=None, build=None)
```

It is allowed to concatenate different “bump functions”:

```
>>> ver.bump_major().bump_minor()
VersionInfo(major=4, minor=1, patch=0, prerelease=None, build=None)
```

To compare two versions, `semver` provides the `semver.compare` function. The return value indicates the relationship between the first and second version:

```
>>> semver.compare("1.0.0", "2.0.0")
-1
>>> semver.compare("2.0.0", "1.0.0")
1
>>> semver.compare("2.0.0", "2.0.0")
0
```

There are other functions to discover. Read on!

2.1 Pip

For Python 2:

```
pip install semver
```

For Python 3:

```
pip3 install semver
```

If you want to install this specific version, you can use the command **pip** with an URL:

```
pip3 install git+https://github.com/python-semver/python-semver.git@|version|
```

2.2 Linux Distributions

Note: Some Linux distributions can have outdated packages. These outdated packages does not contain the latest bug fixes or new features. If you need a newer package, you have these option:

- Ask the maintainer to update the package.
 - Update the package for your favorite distribution and submit it.
 - Use a Python virtual environment and **pip install**.
-

2.2.1 Arch Linux

1. Enable the community repositories first:

```
[community]
Include = /etc/pacman.d/mirrorlist
```

2. Install the package:

```
$ pacman -Sy python-semver
```

2.2.2 Debian

1. Update the package index:

```
$ sudo apt-get update
```

2. Install the package:

```
$ sudo apt-get install python3-semver
```

2.2.3 Fedora

```
$ dnf install python3-semver
```

2.2.4 FreeBSD

```
$ pkg install py36-semver
```

2.2.5 openSUSE

1. Enable the the `devel:languages:python` repository on the Open Build Service (replace `<VERSION>` with the preferred openSUSE release):

```
$ zypper addrepo https://download.opensuse.org/repositories/devel:/languages:/
python/openSUSE_Leap_<VERSION>/devel:languages:python.repo
```

2. Install the package:

```
$ zypper --repo devel_languages_python python3-semver
```

2.2.6 Ubuntu

1. Update the package index:

```
$ sudo apt-get update
```

2. Install the package:

```
$ sudo apt-get install python3-semver
```


The `semver` module can store a version in the `semver.VersionInfo` class. For historical reasons, a version can be also stored as a string or dictionary.

Each type can be converted into the other, if the minimum requirements are met.

3.1 Knowing the Implemented semver.org Version

The `semver.org` page is the authoritative specification of how semantical versioning is defined. To know which version of `semver.org` is implemented in the `semver` library, use the following constant:

```
>>> semver.SEMVER_SPEC_VERSION
'2.0.0'
```

3.2 Creating a Version

Due to historical reasons, the `semver` project offers two ways of creating a version:

- through an object oriented approach with the `semver.VersionInfo` class. This is the preferred method when using `semver`.
- through module level functions and builtin datatypes (usually string and dict). This method is still available for compatibility reasons, but are marked as deprecated. Using it will emit a `DeprecationWarning`.

Warning: Deprecation Warning

Module level functions are marked as *deprecated* in version 2.10.0 now. These functions will be removed in `semver` 3. For details, see the sections [Replacing Deprecated Functions](#) and [Displaying Deprecation Warnings](#).

A `semver.VersionInfo` instance can be created in different ways:

- From a string:

```
>>> semver.VersionInfo.parse("3.4.5-pre.2+build.4")
VersionInfo(major=3, minor=4, patch=5, prerelease='pre.2', build='build.4')
```

- From individual parts by a dictionary:

```
>>> d = {'major': 3, 'minor': 4, 'patch': 5, 'prerelease': 'pre.2', 'build':
↳ 'build.4'}
>>> semver.VersionInfo(**d)
VersionInfo(major=3, minor=4, patch=5, prerelease='pre.2', build='build.4')
```

As a minimum requirement, your dictionary needs at least the `major` key, others can be omitted. You get a `TypeError` if your dictionary contains invalid keys. Only the keys `major`, `minor`, `patch`, `prerelease`, and `build` are allowed.

- From a tuple:

```
>>> t = (3, 5, 6)
>>> semver.VersionInfo(*t)
VersionInfo(major=3, minor=5, patch=6, prerelease=None, build=None)
```

You can pass either an integer or a string for `major`, `minor`, or `patch`:

```
>>> semver.VersionInfo("3", "5", 6)
VersionInfo(major=3, minor=5, patch=6, prerelease=None, build=None)
```

The old, deprecated module level functions are still available. If you need them, they return different builtin objects (string and dictionary). Keep in mind, once you have converted a version into a string or dictionary, it's an ordinary builtin object. It's not a special version object like the `semver.VersionInfo` class anymore.

Depending on your use case, the following methods are available:

- From individual version parts into a string

In some cases you only need a string from your version data:

```
>>> semver.format_version(3, 4, 5, 'pre.2', 'build.4')
'3.4.5-pre.2+build.4'
```

- From a string into a dictionary

To access individual parts, you can use the function `semver.parse()`:

```
>>> semver.parse("3.4.5-pre.2+build.4")
OrderedDict([('major', 3), ('minor', 4), ('patch', 5), ('prerelease', 'pre.2'), (
↳ 'build', 'build.4')])
```

If you pass an invalid version string you will get a `ValueError`:

```
>>> semver.parse("1.2")
Traceback (most recent call last):
...
ValueError: 1.2 is not valid SemVer string
```

3.3 Parsing a Version String

“Parsing” in this context means to identify the different parts in a string.

- With `semver.parse_version_info()`:

```
>>> semver.parse_version_info("3.4.5-pre.2+build.4")
VersionInfo(major=3, minor=4, patch=5, prerelease='pre.2', build='build.4')
```

- With `semver.VersionInfo.parse()` (basically the same as `semver.parse_version_info()`):

```
>>> semver.VersionInfo.parse("3.4.5-pre.2+build.4")
VersionInfo(major=3, minor=4, patch=5, prerelease='pre.2', build='build.4')
```

- With `semver.parse()`:

```
>>> semver.parse("3.4.5-pre.2+build.4") == {'major': 3, 'minor': 4, 'patch': 5,
↳ 'prerelease': 'pre.2', 'build': 'build.4'}
True
```

3.4 Checking for a Valid Semver Version

If you need to check a string if it is a valid semver version, use the classmethod `semver.VersionInfo.isvalid()`:

```
>>> semver.VersionInfo.isvalid("1.0.0")
True
>>> semver.VersionInfo.isvalid("invalid")
False
```

3.5 Accessing Parts of a Version Through Names

The `semver.VersionInfo` contains attributes to access the different parts of a version:

```
>>> v = semver.VersionInfo.parse("3.4.5-pre.2+build.4")
>>> v.major
3
>>> v.minor
4
>>> v.patch
5
>>> v.prerelease
'pre.2'
>>> v.build
'build.4'
```

However, the attributes are read-only. You cannot change an attribute. If you do, you get an `AttributeError`:

```
>>> v.minor = 5
Traceback (most recent call last):
...
AttributeError: attribute 'minor' is readonly
```

If you need to replace different parts of a version, refer to section [Replacing Parts of a Version](#).

In case you need the different parts of a version stepwise, iterate over the `semver.VersionInfo` instance:

```
>>> for item in semver.VersionInfo.parse("3.4.5-pre.2+build.4"):  
...     print(item)  
3  
4  
5  
pre.2  
build.4  
>>> list(semver.VersionInfo.parse("3.4.5-pre.2+build.4"))  
[3, 4, 5, 'pre.2', 'build.4']
```

3.6 Accessing Parts Through Index Numbers

New in version 2.10.0.

Another way to access parts of a version is to use an index notation. The underlying *VersionInfo* object allows to access its data through the magic method `__getitem__`.

For example, the major part can be accessed by index number 0 (zero). Likewise the other parts:

```
>>> ver = semver.VersionInfo.parse("10.3.2-pre.5+build.10")  
>>> ver[0], ver[1], ver[2], ver[3], ver[4]  
(10, 3, 2, 'pre.5', 'build.10')
```

If you need more than one part at the same time, use the slice notation:

```
>>> ver[0:3]  
(10, 3, 2)
```

Or, as an alternative, you can pass a `slice()` object:

```
>>> sl = slice(0,3)  
>>> ver[sl]  
(10, 3, 2)
```

Negative numbers or undefined parts raise an `IndexError` exception:

```
>>> ver = semver.VersionInfo.parse("10.3.2")  
>>> ver[3]  
Traceback (most recent call last):  
...  
IndexError: Version part undefined  
>>> ver[-2]  
Traceback (most recent call last):  
...  
IndexError: Version index cannot be negative
```

3.7 Replacing Parts of a Version

If you want to replace different parts of a version, but leave other parts unmodified, use the function `semver.VersionInfo.replace()` or `semver.replace()`:

- From a `semver.VersionInfo` instance:

```
>>> version = semver.VersionInfo.parse("1.4.5-pre.1+build.6")
>>> version.replace(major=2, minor=2)
VersionInfo(major=2, minor=2, patch=5, prerelease='pre.1', build='build.6')
```

- From a version string:

```
>>> semver.replace("1.4.5-pre.1+build.6", major=2)
'2.4.5-pre.1+build.6'
```

If you pass invalid keys you get an exception:

```
>>> semver.replace("1.2.3", invalidkey=2)
Traceback (most recent call last):
...
TypeError: replace() got 1 unexpected keyword argument(s): invalidkey
>>> version = semver.VersionInfo.parse("1.4.5-pre.1+build.6")
>>> version.replace(invalidkey=2)
Traceback (most recent call last):
...
TypeError: replace() got 1 unexpected keyword argument(s): invalidkey
```

3.8 Converting a VersionInfo instance into Different Types

Sometimes it is needed to convert a `semver.VersionInfo` instance into a different type. For example, for displaying or to access all parts.

It is possible to convert a `semver.VersionInfo` instance:

- Into a string with the builtin function `str()`:

```
>>> str(semver.VersionInfo.parse("3.4.5-pre.2+build.4"))
'3.4.5-pre.2+build.4'
```

- Into a dictionary with `semver.VersionInfo.to_dict()`:

```
>>> v = semver.VersionInfo(major=3, minor=4, patch=5)
>>> v.to_dict()
OrderedDict([('major', 3), ('minor', 4), ('patch', 5), ('prerelease', None), (
  ↳ 'build', None)])
```

- Into a tuple with `semver.VersionInfo.to_tuple()`:

```
>>> v = semver.VersionInfo(major=5, minor=4, patch=2)
>>> v.to_tuple()
(5, 4, 2, None, None)
```

3.9 Raising Parts of a Version

The `semver` module contains the following functions to raise parts of a version:

- `semver.VersionInfo.bump_major()`: raises the major part and set all other parts to zero. Set prerelease and build to `None`.

- `semver.VersionInfo.bump_minor()`: raises the minor part and sets patch to zero. Set prerelease and build to None.
- `semver.VersionInfo.bump_patch()`: raises the patch part. Set prerelease and build to None.
- `semver.VersionInfo.bump_prerelease()`: raises the prerelease part and set build to None.
- `semver.VersionInfo.bump_build()`: raises the build part.

```
>>> str(semver.VersionInfo.parse("3.4.5-pre.2+build.4").bump_major())
'4.0.0'
>>> str(semver.VersionInfo.parse("3.4.5-pre.2+build.4").bump_minor())
'3.5.0'
>>> str(semver.VersionInfo.parse("3.4.5-pre.2+build.4").bump_patch())
'3.4.6'
>>> str(semver.VersionInfo.parse("3.4.5-pre.2+build.4").bump_prerelease())
'3.4.5-pre.3'
>>> str(semver.VersionInfo.parse("3.4.5-pre.2+build.4").bump_build())
'3.4.5-pre.2+build.5'
```

Likewise the module level functions `semver.bump_major()`.

3.10 Increasing Parts of a Version Taking into Account Prereleases

New in version 2.10.0: Added `semver.VersionInfo.next_version()`.

If you want to raise your version and take prereleases into account, the function `semver.VersionInfo.next_version()` would perhaps a better fit.

```
>>> v = semver.VersionInfo.parse("3.4.5-pre.2+build.4")
>>> str(v.next_version(part="prerelease"))
'3.4.5-pre.3'
>>> str(semver.VersionInfo.parse("3.4.5-pre.2+build.4").next_version(part="patch"))
'3.4.5'
>>> str(semver.VersionInfo.parse("3.4.5+build.4").next_version(part="patch"))
'3.4.5'
>>> str(semver.VersionInfo.parse("0.1.4").next_version("prerelease"))
'0.1.5-rc.1'
```

3.11 Comparing Versions

To compare two versions depends on your type:

- **Two strings**

Use `semver.compare()`:

```
>>> semver.compare("1.0.0", "2.0.0")
-1
>>> semver.compare("2.0.0", "1.0.0")
1
>>> semver.compare("2.0.0", "2.0.0")
0
```

The return value is negative if `version1 < version2`, zero if `version1 == version2` and strictly positive if `version1 > version2`.

- **Two `semver.VersionInfo` instances**

Use the specific operator. Currently, the operators `<`, `<=`, `>`, `>=`, `==`, and `!=` are supported:

```
>>> v1 = semver.VersionInfo.parse("3.4.5")
>>> v2 = semver.VersionInfo.parse("3.5.1")
>>> v1 < v2
True
>>> v1 > v2
False
```

- **A `semver.VersionInfo` type and a `tuple()` or `list()`**

Use the operator as with two `semver.VersionInfo` types:

```
>>> v = semver.VersionInfo.parse("3.4.5")
>>> v > (1, 0)
True
>>> v < [3, 5]
True
```

The opposite does also work:

```
>>> (1, 0) < v
True
>>> [3, 5] > v
True
```

- **A `semver.VersionInfo` type and a `str()`**

You can use also raw strings to compare:

```
>>> v > "1.0.0"
True
>>> v < "3.5.0"
True
```

The opposite does also work:

```
>>> "1.0.0" < v
True
>>> "3.5.0" > v
True
```

However, if you compare incomplete strings, you get a `ValueError` exception:

```
>>> v > "1.0"
Traceback (most recent call last):
...
ValueError: 1.0 is not valid SemVer string
```

- **A `semver.VersionInfo` type and a `dict()`**

You can also use a dictionary. In contrast to strings, you can have an “incomplete” version (as the other parts are set to zero):

```
>>> v > dict(major=1)
True
```

The opposite does also work:

```
>>> dict(major=1) < v
True
```

If the dictionary contains unknown keys, you get a `TypeError` exception:

```
>>> v > dict(major=1, unknown=42)
Traceback (most recent call last):
...
TypeError: __init__() got an unexpected keyword argument 'unknown'
```

Other types cannot be compared.

If you need to convert some types into other, refer to *Converting a `VersionInfo` instance into Different Types*.

3.12 Comparing Versions through an Expression

If you need a more fine-grained approach of comparing two versions, use the `semver.match()` function. It expects two arguments:

1. a version string
2. a match expression

Currently, the match expression supports the following operators:

- `<` smaller than
- `>` greater than
- `>=` greater or equal than
- `<=` smaller or equal than
- `==` equal
- `!=` not equal

That gives you the following possibilities to express your condition:

```
>>> semver.match("2.0.0", ">=1.0.0")
True
>>> semver.match("1.0.0", ">1.0.0")
False
```

3.13 Getting Minimum and Maximum of two Versions

```
>>> semver.max_ver("1.0.0", "2.0.0")
'2.0.0'
>>> semver.min_ver("1.0.0", "2.0.0")
'1.0.0'
```

3.14 Dealing with Invalid Versions

As semver follows the semver specification, it cannot parse version strings which are considered “invalid” by that specification. The semver library cannot know all the possible variations so you need to help the library a bit.

For example, if you have a version string `v1.2` would be an invalid semver version. However, “basic” version strings consisting of major, minor, and patch part, can be easy to convert. The following function extract this information and returns a tuple with two items:

```
import re
import semver

BASEVERSION = re.compile(
    r"""[vV]?
        (?P<major>0|[1-9]\d*)
        (\.
        (?P<minor>0|[1-9]\d*)
        (\.
        (?P<patch>0|[1-9]\d*)
        )?
        )?
    """,
    re.VERBOSE,
)

def coerce(version):
    """
    Convert an incomplete version string into a semver-compatible VersionInfo
    object

    * Tries to detect a "basic" version string (`major.minor.patch`).
    * If not enough components can be found, missing components are
      set to zero to obtain a valid semver version.

    :param str version: the version string to convert
    :return: a tuple with a :class:`VersionInfo` instance (or ``None``
             if it's not a version) and the rest of the string which doesn't
             belong to a basic version.
    :rtype: tuple(:class:`VersionInfo` | None, str)
    """
    match = BASEVERSION.search(version)
    if not match:
        return (None, version)

    ver = {
        key: 0 if value is None else value for key, value in match.groupdict().items()
    }
    ver = semver.VersionInfo(**ver)
    rest = match.string[match.end():] # noqa:E203
    return ver, rest
```

The function returns a *tuple*, containing a `VersionInfo` instance or `None` as the first element and the rest as the second element. The second element (the rest) can be used to make further adjustments.

For example:

```
>>> coerce("v1.2")
(VersionInfo(major=1, minor=2, patch=0, prerelease=None, build=None), '')
>>> coerce("v2.5.2-bla")
(VersionInfo(major=2, minor=5, patch=2, prerelease=None, build=None), '-bla')
```

3.15 Replacing Deprecated Functions

Changed in version 2.10.0: The development team of semver has decided to deprecate certain functions on the module level. The preferred way of using semver is through the `semver.VersionInfo` class.

The deprecated functions can still be used in version 2.10.0 and above. In version 3 of semver, the deprecated functions will be removed.

The following list shows the deprecated functions and how you can replace them with code which is compatible for future versions:

- `semver.bump_major()`, `semver.bump_minor()`, `semver.bump_patch()`, `semver.bump_prerelease()`, `semver.bump_build()`

Replace them with the respective methods of the `semver.VersionInfo` class. For example, the function `semver.bump_major()` is replaced by `semver.VersionInfo.bump_major()` and calling the `str(versionobject)`:

```
>>> s1 = semver.bump_major("3.4.5")
>>> s2 = str(semver.VersionInfo.parse("3.4.5").bump_major())
>>> s1 == s2
True
```

Likewise with the other module level functions.

- `semver.finalize_version()`

Replace it with `semver.VersionInfo.finalize_version()`:

```
>>> s1 = semver.finalize_version('1.2.3-rc.5')
>>> s2 = str(semver.VersionInfo.parse('1.2.3-rc.5').finalize_version())
>>> s1 == s2
True
```

- `semver.format_version()`

Replace it with `str(versionobject)`:

```
>>> s1 = semver.format_version(5, 4, 3, 'pre.2', 'build.1')
>>> s2 = str(semver.VersionInfo(5, 4, 3, 'pre.2', 'build.1'))
>>> s1 == s2
True
```

- `semver.parse()`

Replace it with `semver.VersionInfo.parse()` and `semver.VersionInfo.to_dict()`:

```
>>> v1 = semver.parse("1.2.3")
>>> v2 = semver.VersionInfo.parse("1.2.3").to_dict()
>>> v1 == v2
True
```

- `semver.parse_version_info()`

Replace it with `semver.VersionInfo.parse()`:

```
>>> v1 = semver.parse_version_info("3.4.5")
>>> v2 = semver.VersionInfo.parse("3.4.5")
>>> v1 == v2
True
```

- `semver.replace()`

Replace it with `semver.VersionInfo.replace()`:

```
>>> s1 = semver.replace("1.2.3", major=2, patch=10)
>>> s2 = str(semver.VersionInfo.parse('1.2.3').replace(major=2, patch=10))
>>> s1 == s2
True
```

3.16 Displaying Deprecation Warnings

By default, deprecation warnings are [ignored in Python](#). This also affects `semver`'s own warnings.

It is recommended that you turn on deprecation warnings in your scripts. Use one of the following methods:

- Use the option `-Wd` to enable default warnings:

- Directly running the Python command:

```
$ python3 -Wd scriptname.py
```

- Add the option in the shebang line (something like `#!/usr/bin/python3`) after the command:

```
#!/usr/bin/python3 -Wd
```

- In your own scripts add a filter to ensure that *all* warnings are displayed:

```
import warnings
warnings.simplefilter("default")
# Call your semver code
```

For further details, see the section [Overriding the default filter](#) of the Python documentation.

4.1 Synopsis

```
pysemver <COMMAND> <OPTION>...
```

4.2 Description

The semver library provides a command line interface with the name **pysemver** to make the functionality accessible for shell scripts. The script supports several subcommands.

4.2.1 Global Options

-h, --help

Display usage summary.

--version

Show program's version number and exit.

4.3 Commands

4.3.1 pysemver bump

Bump a version.

```
pysemver bump <PART> <VERSION>
```

<PART>

The part to bump. Valid strings are `major`, `minor`, `patch`, `prerelease`, or `build`. The part has the following effects:

- `major`: Raise the major part of the version and set minor and patch to zero, remove prerelease and build.
- `minor`: Raise the minor part of the version and set patch to zero, remove prerelease and build.
- `patch`: Raise the patch part of the version and remove prerelease and build.
- `prerelease`: Raise the prerelease of the version and remove the build part.
- `build`: Raise the build part.

<VERSION>

The version to bump.

To bump a version, you pass the name of the part (`major`, `minor`, `patch`, `prerelease`, or `build`) and the version string. The bumped version is printed on standard out:

```
$ pysemver bump major 1.2.3
2.0.0
$ pysemver bump minor 1.2.3
1.3.0
```

If you pass a version string which is not a valid semantical version, you get an error message and a return code `!= 0`:

```
$ pysemver bump build 1.5
ERROR 1.5 is not valid SemVer string
```

4.3.2 pysemver check

Checks if a string is a valid semver version.

```
pysemver check <VERSION>
```

<VERSION>

The version string to check.

The *error code* returned by the script indicates if the version is valid (`=0`) or not (`!=0`):

```
$ pysemver check 1.2.3; echo $?
0
$ pysemver check 2.1; echo $?
ERROR Invalid version '2.1'
2
```

4.3.3 pysemver compare

Compare two versions.

```
pysemver compare <VERSION1> <VERSION2>
```

<VERSION1>

First version

<VERSION2>

Second version

When you compare two versions, the result is printed on *standard out*, to indicates which is the bigger version:

- -1 if first version is smaller than the second version,
- 0 if both versions are the same,
- 1 if the first version is greater than the second version.

4.4 Return Code

The *return code* of the script (accessible by `$?` from the Bash) indicates if the subcommand returned successfully nor not. It is *not* meant as the result of the subcommand.

The result of the subcommand is printed on the standard out channel (“stdout” or 0), any error messages to standard error (“stderr” or 2).

For example, to compare two versions, the command expects two valid semver versions:

```
$ pysemver compare 1.2.3 2.4.0
-1
$ echo $?
0
```

The return code is zero, but the result is -1.

However, if you pass invalid versions, you get this situation:

```
$ pysemver compare 1.2.3 2.4
ERROR 2.4 is not valid SemVer string
$ echo $?
2
```

If you use the **pysemver** in your own scripts, check the return code first before you process the standard output.

4.5 See also

Documentation <https://python-semver.readthedocs.io/>

Source code <https://github.com/python-semver/python-semver>

Bug tracker <https://github.com/python-semver/python-semver/issues>

Contributing to semver

The semver source code is managed using Git and is hosted on GitHub:

```
git clone git://github.com/python-semver/python-semver
```

5.1 Reporting Bugs and Feedback

If you think you have encountered a bug in semver or have an idea for a new feature? Great! We like to hear from you. First, take the time to look into our GitHub [issues](#) tracker if this already covered. If not, changes are good that we avoid double work.

5.2 Fixing Bugs and Implementing New Features

Before you make changes to the code, we would highly appreciate if you consider the following general requirements:

- Make sure your code adheres to the [Semantic Versioning](#) specification.
- Check if your feature is covered by the Semantic Versioning specification. If not, ask on its GitHub project <https://github.com/semver/semver>.
- Write test cases if you implement a new feature.
- Test also for side effects of your new feature and run the complete test suite.
- Document the new feature, see [Documenting semver](#) for details.

5.3 Modifying the Code

We recommend the following workflow:

1. Fork our project on GitHub using this link: <https://github.com/python-semver/python-semver/fork>
2. Clone your forked Git repository (replace `GITHUB_USER` with your account name on GitHub):

```
$ git clone git@github.com:GITHUB_USER/python-semver.git
```

3. Create a new branch. You can name your branch whatever you like, but we recommend to use some meaningful name. If your fix is based on an existing GitHub issue, add also the number. Good examples would be:
 - `feature/123-improve-foo` when implementing a new feature in issue 123
 - `bugfix/234-fix-security-bar` a bugfixes for issue 234

Use this **git** command:

```
$ git checkout -b feature/NAME_OF_YOUR_FEATURE
```

4. Work on your branch. Commit your work.
5. Write test cases and run the test suite, see *Running the Test Suite* for details.
6. Create a [pull request](#). Describe in the pull request what you did and why. If you have open questions, ask.
7. Wait for feedback. If you receive any comments, address these.
8. After your pull request got accepted, delete your branch.
9. Use the `clean` command to remove build and test files and folders:

```
$ python setup.py clean
```

5.4 Running the Test Suite

We use `pytest` and `tox` to run tests against all supported Python versions. All test dependencies are resolved automatically.

You can decide to run the complete test suite or only part of it:

- To run all tests, use:

```
$ tox
```

If you have not all Python interpreters installed on your system it will probably give you some errors (`InterpreterNotFound`). To avoid such errors, use:

```
$ tox --skip-missing-interpreters
```

It is possible to use only specific Python versions. Use the `-e` option and one or more abbreviations (`py27` for Python 2.7, `py34` for Python 3.4 etc.):

```
$ tox -e py34
$ tox -e py27,py34
```

To get a complete list, run:

```
$ tox -l
```

- To run only a specific test, pytest requires the syntax `TEST_FILE::TEST_FUNCTION`.

For example, the following line tests only the function `test_immutable_major()` in the file `test_semver.py` for all Python versions:

```
$ tox test_semver.py::test_immutable_major
```

By default, pytest prints a dot for each test function only. To reveal the executed test function, use the following syntax:

```
$ tox -- -v
```

You can combine the specific test function with the `-e` option, for example, to limit the tests for Python 2.7 and 3.6 only:

```
$ tox -e py27,py36 test_semver.py::test_immutable_major
```

Our code is checked against [flake8](#) for style guide issues. It is recommended to run your tests in combination with **flake8**, for example:

```
$ tox -e py27,py36,flake8
```

5.5 Documenting semver

Documenting the features of semver is very important. It gives our developers an overview what is possible with semver, how it “feels”, and how it is used efficiently.

Note: To build the documentation locally use the following command:

```
$ tox -e docs
```

The built documentation is available in `dist/docs`.

A new feature is *not* complete if it isn’t properly documented. A good documentation includes:

- **A docstring**

Each docstring contains a summary line, a linebreak, the description of its arguments in [Sphinx style](#), and an optional doctest. The docstring is extracted and reused in the [API](#) section. An appropriate docstring should look like this:

```
def compare(ver1, ver2):
    """Compare two versions

    :param ver1: version string 1
    :param ver2: version string 2
    :return: The return value is negative if ver1 < ver2,
             zero if ver1 == ver2 and strictly positive if ver1 > ver2
    :rtype: int

    >>> semver.compare("1.0.0", "2.0.0")
    -1
    >>> semver.compare("2.0.0", "1.0.0")
    1
```

(continues on next page)

(continued from previous page)

```
>>> semver.compare("2.0.0", "2.0.0")
0

"""
```

- **The documentation**

A docstring is good, but in most cases it's too dense. Describe how to use your new feature in our documentation. Here you can give your readers more examples, describe it in a broader context or show edge cases.

Python helper for Semantic Versioning (<http://semver.org/>)

`semver.SEMVER_SPEC_VERSION = '2.0.0'`

Contains the implemented semver.org version of the spec

class `semver.VersionInfo` (*major*, *minor*=0, *patch*=0, *prerelease*=None, *build*=None)

A semver compatible version class.

Parameters

- **major** (*int*) – version when you make incompatible API changes.
- **minor** (*int*) – version when you add functionality in a backwards-compatible manner.
- **patch** (*int*) – version when you make backwards-compatible bug fixes.
- **prerelease** (*str*) – an optional prerelease string
- **build** (*str*) – an optional build string

build

The build part of a version (read-only).

bump_build (*token*='build')

Raise the build part of the version, return a new object but leave self untouched.

Parameters *token* – defaults to 'build'

Returns new object with the raised build part

Return type str

```
>>> ver = semver.VersionInfo.parse("3.4.5-rc.1+build.9")
>>> ver.bump_build()
VersionInfo(major=3, minor=4, patch=5, prerelease='rc.1', build='build.10')
```

bump_major ()

Raise the major part of the version, return a new object but leave self untouched.

Returns new object with the raised major part

Return type *VersionInfo*

```
>>> ver = semver.VersionInfo.parse("3.4.5")
>>> ver.bump_major()
VersionInfo(major=4, minor=0, patch=0, prerelease=None, build=None)
```

bump_minor()

Raise the minor part of the version, return a new object but leave self untouched.

Returns new object with the raised minor part

Return type *VersionInfo*

```
>>> ver = semver.VersionInfo.parse("3.4.5")
>>> ver.bump_minor()
VersionInfo(major=3, minor=5, patch=0, prerelease=None, build=None)
```

bump_patch()

Raise the patch part of the version, return a new object but leave self untouched.

Returns new object with the raised patch part

Return type *VersionInfo*

```
>>> ver = semver.VersionInfo.parse("3.4.5")
>>> ver.bump_patch()
VersionInfo(major=3, minor=4, patch=6, prerelease=None, build=None)
```

bump_prerelease(token='rc')

Raise the prerelease part of the version, return a new object but leave self untouched.

Parameters *token* – defaults to 'rc'

Returns new object with the raised prerelease part

Return type str

```
>>> ver = semver.VersionInfo.parse("3.4.5-rc.1")
>>> ver.bump_prerelease()
VersionInfo(major=3, minor=4, patch=5, prerelease='rc.2', build=None)
```

compare(*other*)

Compare self with other.

Parameters *other* – the second version (can be string, a dict, tuple/list, or a VersionInfo instance)

Returns The return value is negative if `ver1 < ver2`, zero if `ver1 == ver2` and strictly positive if `ver1 > ver2`

Return type int

```
>>> semver.VersionInfo.parse("1.0.0").compare("2.0.0")
-1
>>> semver.VersionInfo.parse("2.0.0").compare("1.0.0")
1
>>> semver.VersionInfo.parse("2.0.0").compare("2.0.0")
0
>>> semver.VersionInfo.parse("2.0.0").compare(dict(major=2, minor=0, patch=0))
0
```

finalize_version()

Remove any prerelease and build metadata from the version.

Returns a new instance with the finalized version string

Return type `VersionInfo`

```
>>> str(semver.VersionInfo.parse('1.2.3-rc.5').finalize_version())
'1.2.3'
```

classmethod isvalid(version)

Check if the string is a valid semver version.

New in version 2.9.1.

Parameters **version** (*str*) – the version string to check

Returns True if the version string is a valid semver version, False otherwise.

Return type bool

major

The major part of a version (read-only).

match(match_expr)

Compare self to match a match expression.

Parameters **match_expr** (*str*) – operator and version; valid operators are < smaller than > greater than >= greater or equal than <= smaller or equal than == equal != not equal

Returns True if the expression matches the version, otherwise False

Return type bool

```
>>> semver.VersionInfo.parse("2.0.0").match(">=1.0.0")
True
>>> semver.VersionInfo.parse("1.0.0").match(">1.0.0")
False
```

minor

The minor part of a version (read-only).

next_version(part, prerelease_token='rc')

Determines next version, preserving natural order.

New in version 2.10.0.

This function is taking prereleases into account. The “major”, “minor”, and “patch” raises the respective parts like the `bump_*` functions. The real difference is using the “prerelease” part. It gives you the next patch version of the prerelease, for example:

```
>>> str(semver.VersionInfo.parse("0.1.4").next_version("prerelease"))
'0.1.5-rc.1'
```

Parameters

- **part** – One of “major”, “minor”, “patch”, or “prerelease”
- **prerelease_token** – prefix string of prerelease, defaults to ‘rc’

Returns

static parse (*version*)

Parse version string to a VersionInfo instance.

Parameters *version* – version string

Returns a `semver.VersionInfo` instance

Raises `ValueError`

Return type `semver.VersionInfo`

```
>>> semver.VersionInfo.parse('3.4.5-pre.2+build.4')
VersionInfo(major=3, minor=4, patch=5, prerelease='pre.2', build='build.4')
```

patch

The patch part of a version (read-only).

prerelease

The prerelease part of a version (read-only).

replace (***parts*)

Replace one or more parts of a version and return a new `semver.VersionInfo` object, but leave self untouched

New in version 2.9.0: Added `VersionInfo.replace()`

Parameters *parts* (*dict*) – the parts to be updated. Valid keys are: `major`, `minor`, `patch`, `prerelease`, or `build`

Returns the new `semver.VersionInfo` object with the changed parts

Raises `TypeError`, if *parts* contains invalid keys

to_dict ()

Convert the VersionInfo object to an OrderedDict.

New in version 2.10.0: Renamed `VersionInfo._asdict` to `VersionInfo.to_dict` to make this function available in the public API.

Returns an OrderedDict with the keys in the order `major`, `minor`, `patch`, `prerelease`, and `build`.

Return type `collections.OrderedDict`

```
>>> semver.VersionInfo(3, 2, 1).to_dict()
OrderedDict([('major', 3), ('minor', 2), ('patch', 1), ('prerelease', None), (
↪ 'build', None)])
```

to_tuple ()

Convert the VersionInfo object to a tuple.

New in version 2.10.0: Renamed `VersionInfo._astuple` to `VersionInfo.to_tuple` to make this function available in the public API.

Returns a tuple with all the parts

Return type `tuple`

```
>>> semver.VersionInfo(5, 3, 1).to_tuple()
(5, 3, 1, None, None)
```

semver.bump_build (**args*, ***kwargs*)

Raise the build part of the version string.

Deprecated since version 2.10.0: Use `semver.VersionInfo.bump_build()` instead.

Parameters

- **version** – version string
- **token** – defaults to 'build'

Returns the raised version string

Return type str

```
>>> semver.bump_build('3.4.5-rc.1+build.9')
'3.4.5-rc.1+build.10'
```

`semver.bump_major(*args, **kwargs)`

Raise the major part of the version string.

Deprecated since version 2.10.0: Use `semver.VersionInfo.bump_major()` instead.

Param version string

Returns the raised version string

Return type str

```
>>> semver.bump_major("3.4.5")
'4.0.0'
```

`semver.bump_minor(*args, **kwargs)`

Raise the minor part of the version string.

Deprecated since version 2.10.0: Use `semver.VersionInfo.bump_minor()` instead.

Param version string

Returns the raised version string

Return type str

```
>>> semver.bump_minor("3.4.5")
'3.5.0'
```

`semver.bump_patch(*args, **kwargs)`

Raise the patch part of the version string.

Deprecated since version 2.10.0: Use `semver.VersionInfo.bump_patch()` instead.

Param version string

Returns the raised version string

Return type str

```
>>> semver.bump_patch("3.4.5")
'3.4.6'
```

`semver.bump_prerelease(*args, **kwargs)`

Raise the prerelease part of the version string.

Deprecated since version 2.10.0: Use `semver.VersionInfo.bump_prerelease()` instead.

Parameters

- **version** – version string

- **token** – defaults to 'rc'

Returns the raised version string

Return type str

```
>>> semver.bump_prerelease('3.4.5', 'dev')
'3.4.5-dev.1'
```

`semver.cmd_bump(args)`

Subcommand: Bumps a version.

Synopsis: bump <PART> <VERSION> <PART> can be major, minor, patch, prerelease, or build

Parameters **args** (argparse.Namespace) – The parsed arguments

Returns the new, bumped version

`semver.cmd_check(args)`

Subcommand: Checks if a string is a valid semver version.

Synopsis: check <VERSION>

Parameters **args** (argparse.Namespace) – The parsed arguments

`semver.cmd_compare(args)`

Subcommand: Compare two versions

Synopsis: compare <VERSION1> <VERSION2>

Parameters **args** (argparse.Namespace) – The parsed arguments

`semver.cmd_nextver(args)`

Subcommand: Determines the next version, taking prereleases into account.

Synopsis: nextver <VERSION> <PART>

Parameters **args** (argparse.Namespace) – The parsed arguments

`semver.cmp(a, b)`

Return negative if a<b, zero if a==b, positive if a>b.

`semver.comparator(operator)`

Wrap a VersionInfo binary op method in a type-check.

`semver.compare(*args, **kwargs)`

Compare two versions strings.

Parameters

- **ver1** – version string 1
- **ver2** – version string 2

Returns The return value is negative if ver1 < ver2, zero if ver1 == ver2 and strictly positive if ver1 > ver2

Return type int

```
>>> semver.compare("1.0.0", "2.0.0")
-1
>>> semver.compare("2.0.0", "1.0.0")
1
>>> semver.compare("2.0.0", "2.0.0")
0
```

`semver.createparser()`

Create an `argparse.ArgumentParser` instance.

Returns parser instance

Return type `argparse.ArgumentParser`

`semver.deprecated(func=None, replace=None, version=None, category=<type 'exceptions.DeprecationWarning'>)`

Decorates a function to output a deprecation warning.

Parameters

- **func** – the function to decorate (or None)
- **replace** (*str*) – the function to replace (use the full qualified name like `semver.VersionInfo.bump_major`).
- **version** (*str*) – the first version when this function was deprecated.
- **category** – allow you to specify the deprecation warning class of your choice. By default, it's `DeprecationWarning`, but you can choose `PendingDeprecationWarning` or a custom class.

`semver.finalize_version(*args, **kwargs)`

Remove any prerelease and build metadata from the version string.

New in version 2.7.9: Added `finalize_version()`

Deprecated since version 2.10.0: Use `semver.VersionInfo.finalize_version()` instead.

Parameters **version** – version string

Returns the finalized version string

Return type `str`

```
>>> semver.finalize_version('1.2.3-rc.5')
'1.2.3'
```

`semver.format_version(*args, **kwargs)`

Format a version string according to the Semantic Versioning specification.

Deprecated since version 2.10.0: Use `str(VersionInfo(VERSION))` instead.

Parameters

- **major** (*int*) – the required major part of a version
- **minor** (*int*) – the required minor part of a version
- **patch** (*int*) – the required patch part of a version
- **prerelease** (*str*) – the optional prerelease part of a version
- **build** (*str*) – the optional build part of a version

Returns the formatted string

Return type `str`

```
>>> semver.format_version(3, 4, 5, 'pre.2', 'build.4')
'3.4.5-pre.2+build.4'
```

`semver.main(cliargs=None)`

Entry point for the application script.

Parameters `cliargs` (*list*) – Arguments to parse or None (=use `sys.argv`)

Returns error code

Return type `int`

`semver.match(*args, **kwargs)`

Compare two versions strings through a comparison.

Parameters

- **version** (*str*) – a version string
- **match_expr** (*str*) – operator and version; valid operators are < smaller than > greater than >= greater or equal than <= smaller or equal than == equal != not equal

Returns True if the expression matches the version, otherwise False

Return type `bool`

```
>>> semver.match("2.0.0", ">=1.0.0")
True
>>> semver.match("1.0.0", ">1.0.0")
False
```

`semver.max_ver(ver1, ver2)`

Returns the greater version of two versions strings.

Parameters

- **ver1** – version string 1
- **ver2** – version string 2

Returns the greater version of the two

Return type `VersionInfo`

```
>>> semver.max_ver("1.0.0", "2.0.0")
'2.0.0'
```

`semver.min_ver(ver1, ver2)`

Returns the smaller version of two versions strings.

Parameters

- **ver1** – version string 1
- **ver2** – version string 2

Returns the smaller version of the two

Return type `VersionInfo`

```
>>> semver.min_ver("1.0.0", "2.0.0")
'1.0.0'
```

`semver.parse(*args, **kwargs)`

Parse version to major, minor, patch, pre-release, build parts.

Deprecated since version 2.10.0: Use `semver.VersionInfo.parse()` instead.

Parameters **version** – version string

Returns dictionary with the keys ‘build’, ‘major’, ‘minor’, ‘patch’, and ‘prerelease’. The prerelease or build keys can be None if not provided

Return type dict

```
>>> ver = semver.parse('3.4.5-pre.2+build.4')
>>> ver['major']
3
>>> ver['minor']
4
>>> ver['patch']
5
>>> ver['prerelease']
'pre.2'
>>> ver['build']
'build.4'
```

`semver.parse_version_info(*args, **kwargs)`

Parse version string to a `VersionInfo` instance.

Deprecated since version 2.10.0: Use `semver.VersionInfo.parse()` instead.

New in version 2.7.2: Added `semver.parse_version_info()`

Parameters `version` – version string

Returns a `VersionInfo` instance

Return type `VersionInfo`

```
>>> version_info = semver.VersionInfo.parse("3.4.5-pre.2+build.4")
>>> version_info.major
3
>>> version_info.minor
4
>>> version_info.patch
5
>>> version_info.prerelease
'pre.2'
>>> version_info.build
'build.4'
```

`semver.process(args)`

Process the input from the CLI.

Parameters

- **args** (`argparse.Namespace`) – The parsed arguments
- **parser** (`argparse.ArgumentParser`) – the parser instance

Returns result of the selected action

Return type str

`semver.replace(*args, **kwargs)`

Replace one or more parts of a version and return the new string.

New in version 2.9.0: Added `replace()`

Deprecated since version 2.10.0: Use `semver.VersionInfo.replace()` instead.

Parameters

- **version** (`str`) – the version string to replace

- **parts** (*dict*) – the parts to be updated. Valid keys are: `major`, `minor`, `patch`, `prerelease`, or `build`

Returns the replaced version string

Raises `TypeError`, if `parts` contains invalid keys

Return type `str`

```
>>> import semver
>>> semver.replace("1.2.3", major=2, patch=10)
'2.2.10'
```

All notable changes to this code base will be documented in this file, in every released version.

7.1 Version 2.10.0

Released 2020-05-05

Maintainer Tom Schraitle

7.1.1 Features

- **PR #138:** Added `__getitem__` magic method to `semver.VersionInfo` class. Allows to access a version like `version[1]`.
- **PR #235:** Improved documentation and shift focus on `semver.VersionInfo` instead of advertising the old and deprecated module-level functions.

7.1.2 Bug Fixes

- **#224 (PR #226):** In `setup.py`, replaced in class `Clean`, `super(CleanCommand, self).run()` with `CleanCommand.run(self)`
- **#244 (PR #245):** Allow comparison with `VersionInfo`, tuple/list, dict, and string.

7.1.3 Additions

- **PR #228:** Added better doctest integration

7.1.4 Removals

- #225 (PR #229): Output a DeprecationWarning for the following functions:
 - `semver.parse`
 - `semver.parse_version_info`
 - `semver.format_version`
 - `semver.bump_{major,minor,patch,prerelease,build}`
 - `semver.finalize_version`
 - `semver.replace`
 - `semver.VersionInfo._asdict` (use the new, public available function `semver.VersionInfo.to_dict()`)
 - `semver.VersionInfo._astuple` (use the new, public available function `semver.VersionInfo.to_tuple()`)

These deprecated functions will be removed in semver 3.

7.2 Version 2.9.1

Released 2020-02-16

Maintainer Tom Schraitle

7.2.1 Features

- #177 (PR #178): Fixed repository and CI links (moved <https://github.com/k-bx/python-semver/> repository to <https://github.com/python-semver/python-semver/>)
- PR #179: Added note about moving this project to the new python-semver organization on GitHub
- #187 (PR #188): Added logo for python-semver organization and documentation
- #191 (PR #194): Created manpage for pysemver
- #196 (PR #197): Added distribution specific installation instructions
- #201 (PR #202): Reformatted source code with black
- #208 (PR #209): Introduce new function `semver.VersionInfo.isvalid()` and extend **pysemver** with **check** subcommand
- #210 (PR #215): Document how to deal with invalid versions
- PR #212: Improve docstrings according to PEP257

7.2.2 Bug Fixes

- #192 (PR #193): Fixed “pysemver” and “pysemver bump” when called without arguments

7.2.3 Removals

not available

7.3 Version 2.9.0

Released 2019-10-30

Maintainer Sébastien Celles <s.celles@gmail.com>

7.3.1 Features

- #59 (PR #164): Implemented a command line interface
- #85 (PR #147, PR #154): Improved contribution section
- #104 (PR #125): Added iterator to `semver.VersionInfo()`
- #112, #113: Added Python 3.7 support
- PR #120: Improved `test_immutable` function with properties
- PR #125: Created `setup.cfg` for pytest and tox
- #126 (PR #127): Added target for documentation in `tox.ini`
- #142 (PR #143): Improved usage section
- #144 (PR #156): Added `semver.replace()` and `semver.VersionInfo.replace()` functions
- #145 (PR #146): Added posargs in `tox.ini`
- PR #157: Introduce `confest.py` to improve doctests
- PR #165: Improved code coverage
- PR #166: Reworked `.gitignore` file
- #167 (PR #168): Introduced global constant `SEMVER_SPEC_VERSION`

7.3.2 Bug Fixes

- #102: Fixed comparison between `VersionInfo` and tuple
- #103: Disallow comparison between `VersionInfo` and string (and int)
- #121 (PR #122): Use python3 instead of python3.4 in `tox.ini`
- PR #123: Improved `__repr__()` and derive class name from `type()`
- #128 (PR #129): Fixed wrong datatypes in docstring for `semver.format_version()`
- #135 (PR #140): Converted prerelease and build to string
- #136 (PR #151): Added testsuite to tarball
- #154 (PR #155): Improved README description

7.3.3 Removals

- #111 (PR #110): Dropped Python 3.3
- #148 (PR #149): Removed and replaced `python setup.py test`

7.4 Version 2.8.2

Released 2019-05-19

Maintainer Sébastien Celles <s.celles@gmail.com>

Skipped, not released.

7.5 Version 2.8.1

Released 2018-07-09

Maintainer Sébastien Celles <s.celles@gmail.com>

7.5.1 Features

- [#40 \(PR #88\)](#): Added a static parse method to VersionInfo
- [#77 \(PR #47\)](#): Converted multiple tests into `pytest.mark.parametrize`
- [#87, #94 \(PR #93\)](#): Removed named tuple inheritance.
- [#89 \(PR #90\)](#): Added doctests.

7.5.2 Bug Fixes

- [#98 \(PR #99\)](#): Set prerelease and build to None by default
- [#96 \(PR #97\)](#): Made VersionInfo immutable

7.6 Version 2.8.0

Released 2018-05-16

Maintainer Sébastien Celles <s.celles@gmail.com>

7.6.1 Changes

- [#82 \(PR #83\)](#): Renamed `test.py` to `test_semver.py` so `py.test` can autodiscover test file

7.6.2 Additions

- [#79 \(PR #81, PR #84\)](#): Defined and improve a release procedure file
- [#72, #73 \(PR #75\)](#): Implemented `__str__()` and `__hash__()`

7.6.3 Removals

- [#76 \(PR #80\)](#): Removed Python 2.6 compatibility

7.7 Version 2.7.9

Released 2017-09-23

Maintainer Kostiantyn Rybnikov <k-bx@k-bx.com>

7.7.1 Additions

- #65 (PR #66): Added `semver.finalize_version()` function.

7.8 Version 2.7.8

Released 2017-08-25

Maintainer Kostiantyn Rybnikov <k-bx@k-bx.com>

- #62: Support custom default names for pre and build

7.9 Version 2.7.7

Released 2017-05-25

Maintainer Kostiantyn Rybnikov <k-bx@k-bx.com>

- #54 (PR #55): Added comparison between VersionInfo objects
- PR #56: Added support for Python 3.6

7.10 Version 2.7.2

Released 2016-11-08

Maintainer Kostiantyn Rybnikov <k-bx@k-bx.com>

7.10.1 Additions

- Added `semver.parse_version_info()` to parse a version string to a version info tuple.

7.10.2 Bug Fixes

- #37: Removed trailing zeros from prelease doesn't allow to parse 0 pre-release version
- Refine parsing to conform more strictly to SemVer 2.0.0.
SemVer 2.0.0 specification §9 forbids leading zero on identifiers in the prerelease version.

7.11 Version 2.6.0

Released 2016-06-08

Maintainer Kostiantyn Rybnikov <k-bx@k-bx.com>

7.11.1 Removals

- Remove comparison of build component.
SemVer 2.0.0 specification recommends that build component is ignored in comparisons.

7.12 Version 2.5.0

Released 2016-05-25

Maintainer Kostiantyn Rybnikov <k-bx@k-bx.com>

7.12.1 Additions

- Support matching 'not equal' with "!=".

7.12.2 Changes

- Made separate builds for tests on Travis CI.

7.13 Version 2.4.2

Released 2016-05-16

Maintainer Kostiantyn Rybnikov <k-bx@k-bx.com>

7.13.1 Changes

- Migrated README document to reStructuredText format.
- Used Setuptools for distribution management.
- Migrated test cases to Py.test.
- Added configuration for Tox test runner.

7.14 Version 2.4.1

Released 2016-03-04

Maintainer Kostiantyn Rybnikov <k-bx@k-bx.com>

7.14.1 Additions

- [#23](#): Compared build component of a version.

7.15 Version 2.4.0

Released 2016-02-12

Maintainer Kostiantyn Rybnikov <k-bx@k-bx.com>

7.15.1 Bug Fixes

- [#21](#): Compared alphanumeric components correctly.

7.16 Version 2.3.1

Released 2016-01-30

Maintainer Kostiantyn Rybnikov <k-bx@k-bx.com>

7.16.1 Additions

- Declared granted license name in distribution metadata.

7.17 Version 2.3.0

Released 2016-01-29

Maintainer Kostiantyn Rybnikov <k-bx@k-bx.com>

7.17.1 Additions

- Added functions to increment prerelease and build components in a version.

7.18 Version 2.2.1

Released 2015-08-04

Maintainer Kostiantyn Rybnikov <k-bx@k-bx.com>

7.18.1 Bug Fixes

- Corrected comparison when any component includes zero.

7.19 Version 2.2.0

Released 2015-06-21

Maintainer Kostiantyn Rybnikov <k-bx@k-bx.com>

7.19.1 Additions

- Add functions to determined minimum and maximum version.
- Add code examples for recently-added functions.

7.20 Version 2.1.2

Released 2015-05-23

Maintainer Kostiantyn Rybnikov <k-bx@k-bx.com>

7.20.1 Bug Fixes

- Restored current README document to distribution manifest.

7.21 Version 2.1.1

Released 2015-05-23

Maintainer Kostiantyn Rybnikov <k-bx@k-bx.com>

7.21.1 Bug Fixes

- Removed absent document from distribution manifest.

7.22 Version 2.1.0

Released 2015-05-22

Maintainer Kostiantyn Rybnikov <k-bx@k-bx.com>

7.22.1 Additions

- Documented installation instructions.
- Documented project home page.
- Added function to format a version string from components.
- Added functions to increment specific components in a version.

7.22.2 Changes

- Migrated README document to Markdown format.

7.22.3 Bug Fixes

- Corrected code examples in README document.

7.23 Version 2.0.2

Released 2015-04-14

Maintainer Konstantine Rybnikov <k-bx@k-bx.com>

7.23.1 Additions

- Added configuration for Travis continuous integration.
- Explicitly declared supported Python versions.

7.24 Version 2.0.1

Released 2014-09-24

Maintainer Konstantine Rybnikov <k-bx@k-bx.com>

7.24.1 Bug Fixes

- #9: Fixed comparison of equal version strings.

7.25 Version 2.0.0

Released 2014-05-24

Maintainer Konstantine Rybnikov <k-bx@k-bx.com>

7.25.1 Additions

- Grant license in this code base under BSD 3-clause license terms.

7.25.2 Changes

- Update parser to SemVer standard 2.0.0.
- Ignore build component for comparison.

7.26 Version 0.0.2

Released 2012-05-10

Maintainer Konstantine Rybnikov <k-bx@k-bx.com>

7.26.1 Changes

- Use standard library Distutils for distribution management.

7.27 Version 0.0.1

Released 2012-04-28

Maintainer Konstantine Rybnikov <kost-bebix@yandex.ru>

- Initial release.

CHAPTER 8

Indices and Tables

- `genindex`
- `modindex`
- `search`

S

semver, [25](#)

Symbols

-version
 pysemver command line option, 17
 -h, -help
 pysemver command line option, 17
 <PART>
 pysemver command line option, 17
 <VERSION1>
 pysemver command line option, 18
 <VERSION2>
 pysemver command line option, 18
 <VERSION>
 pysemver command line option, 18

B

build (*semver.VersionInfo* attribute), 25
 bump_build() (*in module semver*), 28
 bump_build() (*semver.VersionInfo* method), 25
 bump_major() (*in module semver*), 29
 bump_major() (*semver.VersionInfo* method), 25
 bump_minor() (*in module semver*), 29
 bump_minor() (*semver.VersionInfo* method), 26
 bump_patch() (*in module semver*), 29
 bump_patch() (*semver.VersionInfo* method), 26
 bump_prerelease() (*in module semver*), 29
 bump_prerelease() (*semver.VersionInfo* method), 26

C

cmd_bump() (*in module semver*), 30
 cmd_check() (*in module semver*), 30
 cmd_compare() (*in module semver*), 30
 cmd_nextver() (*in module semver*), 30
 cmp() (*in module semver*), 30
 comparator() (*in module semver*), 30
 compare() (*in module semver*), 30
 compare() (*semver.VersionInfo* method), 26
 createparser() (*in module semver*), 30

D

deprecated() (*in module semver*), 31

F

finalize_version() (*in module semver*), 31
 finalize_version() (*semver.VersionInfo* method), 26
 format_version() (*in module semver*), 31

I

isvalid() (*semver.VersionInfo* class method), 27

M

main() (*in module semver*), 31
 major (*semver.VersionInfo* attribute), 27
 match() (*in module semver*), 32
 match() (*semver.VersionInfo* method), 27
 max_ver() (*in module semver*), 32
 min_ver() (*in module semver*), 32
 minor (*semver.VersionInfo* attribute), 27

N

next_version() (*semver.VersionInfo* method), 27

P

parse() (*in module semver*), 32
 parse() (*semver.VersionInfo* static method), 27
 parse_version_info() (*in module semver*), 33
 patch (*semver.VersionInfo* attribute), 28
 prerelease (*semver.VersionInfo* attribute), 28
 process() (*in module semver*), 33
 pysemver command line option
 -version, 17
 -h, -help, 17
 <PART>, 17
 <VERSION1>, 18
 <VERSION2>, 18
 <VERSION>, 18

R

`replace()` (*in module `semver`*), [33](#)

`replace()` (*`semver.VersionInfo` method*), [28](#)

S

`semver` (*module*), [25](#)

`SEMVER_SPEC_VERSION` (*in module `semver`*), [25](#)

T

`to_dict()` (*`semver.VersionInfo` method*), [28](#)

`to_tuple()` (*`semver.VersionInfo` method*), [28](#)

V

`VersionInfo` (*class in `semver`*), [25](#)